



**CAVIBLASTER™**

## Model – 2022-E50/E60 Specifications and Options

<b>SKID</b>	
Dimensions:	
Height	36" / 92 cm
Width	34" / 86 cm
Length	48" / 122 cm
Weight	900 # / 400 kg
Lifting Eyes / Forklift Slots	Yes / Yes

<b>PUMP SYSTEM</b>	
Pressure Pump	Udor Model NX 75/150
Pump Type – Manifold Material	Triplex plunger - brass
Flow Rate	20 gpm / 76 lpm
Pressure	2,200 psi / 152 bar
Hose Diameter - Max. Length	3/4" - 600 LF / 200 m

<b>FEED SYSTEM</b>	
Feed Pump	Pacer Pumps I Series
Pump Material & Type	Stainless steel self-priming centrifugal
Driver	Electric motor
Maximum Lift	20' / 6 m

<b>DRIVE SYSTEM</b>	
NEMA Frame Size	286T
Enclosure	TEFC
Motor Control	Inverter
Control Box (Fiberglass)	NEMA 4X (US) / IP 56 (EU)
Frequency	60 Hz / 50 Hz
Voltage	230-460 (US) / 380-400 (EU)
Power Supply	3 Phase
Rated Output Power	30 HP / 22.4 kW
Speed Rating	1450 RPM
Transmission	Direct Drive

CaviBlaster™ is manufactured by CaviDyne, LLC™. For additional products visit [www.caviblasters.com](http://www.caviblasters.com).

