



CAVIBLASTER™

Model – 2040-E50/E60

Specifications and Options

SKID	
Dimensions:	
Height	42" / 107 cm
Width	48" / 122 cm
Length	56" / 142 cm
Weight	2,400 # / 1,100 kg
Lifting Eyes / Forklift Slots	Yes / Yes

PUMP SYSTEM	
Pressure Pump	CAT Pumps Model 3560
Pump Type – Manifold Material	Triplex plunger – Stainless steel
Flow Rate	20 gpm / 76 lpm
Nozzle Pressure	3,700 psi / 255 bar
Hose Diameter - Max. Length	3/4" - 600 LF / 200 m

FEED SYSTEM	
Feed Pump	Pacer Pumps I Series
Pump Material & Type	Stainless steel self-priming centrifugal
Driver	Electric motor
Maximum Lift	20' / 6 m

DRIVE SYSTEM	
NEMA Frame Size	365T
Enclosure	TEFC
Motor Control	Inverter
Frequency	60 Hz / 50 Hz
Voltage	460 (US) / 380-400 (EU)
Power Supply	3 Phase
Rated Output Power	75 HP / 56 kW
Speed Rating	1200 RPM
Transmission	Direct Drive
Control Box (Fiberglass)	NEMA 4X (US) / IP 56 (EU)

