



CaviBlaster[™]

Model 1030-ROV

Specifications and Options

SKID	
Dimensions:	
Height	10" / 25 cm
Width	22" / 56 cm
Length	22" / 56 cm
Weight	100 # / 45 kg

PUMP SYSTEM	
Pressure Pump	CAT Pumps Model 661D
Pump Type - Manifold Material	Triplex plunger - Stainless steel
Flow Rate	10 gpm / 38 lpm
Rotational Speed	1,429 RPM
Nozzle Pressure	3,000 psi / 207 bar
Hose Diameter	½"

DRIVE SYSTEM	
Motor	Cross Manufacturing 50 Series
Motor Material & Type	Aluminum hydraulic gear motor
Maximum Hydraulic Pressure	3,000 psi / 207 bar
Maximum Motor Speed	3,000 RPM
Standard Hydraulic Flow - Pressure	19 gpm / 72 lpm - 2,160 psi / 149 bar
Alternate Hydraulic Flow - Pressure	16 gpm / 61 lpm - 2,560 psi / 177 bar
Alternate Hydraulic Flow - Pressure	13 gpm / 49 lpm - 3,100 psi / 214 bar

CaviBlaster[™] is manufactured by CaviDyne, LLC[™]. For additional products visit www.caviblast.com.

