



CAVIBLASTER™

Model - 1620 E60/E50

Specifications and Options

SKID	
Dimensions:	
Height	36" / 92 cm
Width	34" / 86 cm
Length	48" / 122 cm
Weight	700 LBS / 320 kg
Lifting Eyes / Fork Slots	Yes / Yes

PUMP SYSTEM	
Pressure Pump	Udor NX 55/200
Pump Material / Type	Brass / Triplex
Flow Rate	16 GPM / 61 lpm
Pressure	2,000 PSI / 138 Bar
Hose Diameter - Max. Length	3/4" / 300 LF – 19 mm/100 m

FEED SYSTEM	
Feed Pump	Centrifugal
Driver	Electric Motor
Flow Rate	60 GPM/230 lpm @ 15'/5 m head

DRIVE SYSTEM	
Electric Motor Frame	286T
Enclosure	TEFC
Motor Control	Inverter
Frequency	60 Hz / 50 Hz
Voltage	230-460(US) / 380-400(EU)
Power Supply	3 Phase
Rated Output Power	25 HP / 18.7 kW
Speed Rating	1450 RPM
Transmission	Direct Drive
Control Box (Fiber Glass)	NEMA 4X (US) / IP 56 (EU)

CaviBlaster™ is manufactured by CaviDyne, LLC™. For additional products visit www.caviblast.com.

